



Instructions for Easy Installation & Assembly



elfa® Gliding Tie and Belt Rack and Valet Rod

Step 1 Install the Gliding Tie and Belt Rack and the Valet Rod

TIP

- The **Tie and Belt Rack** attaches to the bottom of the Ventilated Shelf and pulls out from the shelf. It is designed to allow a Closet Rod to run through it. When using a Closet Rod, the Gliding Tie and Belt Rack should be positioned next to a Shelf Bracket to maximize the hanging space. Allow 36" of clear space below the rack for ties and belts. **(Figure A)**
- The **Valet Rod** goes from front to back. The clothes will take up 24" in width. Allow 36" - 42" of clear space below the rack. When using the Valet Rod, it should be positioned in the middle of a Shelf or centered between the Hanging Standards. **(Figure B)**

- Position the Gliding Tie and Belt Rack or the Valet Rod so that the “U” shaped part faces the front.
- Place the product where you want it to hang under the shelf so that the front and back hooks fit between two front to back shelf wires. **(Figure A)**

Step 2

- Attach the back hook by inserting it at the back of the shelf in between the two wires that run left to right. **(Figure A)**

Step 3

- Attach the front hook by pushing it back and then up to hang it over the top of the first wire from the front of the shelf that runs left to right. **(Figure A)**

TIP

- **To remove the product**, take the front hook off by pushing back and downward. The back hook will then pull straight out of the Shelf.

